




CONCRETE SCREW ANCHOR

NEW



Code No.	Size	Unit price USD/1000PCS	Recommended		Weight (kg)	Qty/Box (pcs)
			tensile load	shear load (Kn)		
CSA37300F	3/8" x 3"	95.29	3.3	5.5	58.20	50
CSA37400F	3/8" x 4"	117.96	3.3	5.5	71.80	50
CSA37500F	3/8" x 5"	140.63	3.3	5.5	85.60	50
CSA37600F	3/8" x 6"	163.46	3.3	5.5	99.50	50
CSA50300F	1/2" x 3"	164.29	5.0	7.8	100.50	25
CSA50400F	1/2" x 4"	205.36	5.0	7.8	124.80	20
CSA50500F	1/2" x 5"	243.19	5.0	7.8	148.30	20
CSA50600F	1/2" x 6"	279.29	5.0	7.8	172.20	20
CSA50612F	1/2" x 6-1/2"	305.57	5.0	7.8	186.60	20

Installation



- Hex head, hex washer head are available.
- Special thread designed to give maximum fixing ability.
- Threading system allows for total removal of anchor from substrate.
- Easy and complete removal for temporary fixings, e.g. scaffolding
- Ideal for large repetitive fastening, e.g. shelving system, hand rail.
- Carbon steel, heat treatment.
- Zinc plated or hot dipper galvanised.

SUZHOU HONGLY HARDWARE CO., LTD.

**Hongly
Hardware**

Tel:+86-512-68091380, +86-512-68091390

Fax:+86-512-68081370 (2 lines),

+852-35199610 (Hong Kong)

E-mail: cxj@fastening.com.cn

Http:// www.anchor.com.cn